

AD-A116 283

ARMY MISSILE COMMAND REDSTONE ARSENAL AL RESEARCH D--ETC F/8 28/6  
FABRICATION OF HOLOGRAPHIC OPTICAL ELEMENTS FOR ACHROMATIC MATC--ETC(U)  
JAN 82 Y 6 GEORGEKUTTY, J 6 DUTHIE

UNCLASSIFIED

DRSHI/RR-82-2-TR

SBI-AD-E950 250

NL

101  
50/50



END  
DATE  
FILMED  
7-82  
DTIC



HP-E950250

12

AD A116283



TECHNICAL REPORT RR-82-2

**FABRICATION OF HOLOGRAPHIC OPTICAL ELEMENTS  
FOR ACHROMATIC MATCHED FILTERING SYSTEM**

T. G. Georgekutty and J. G. Duthie  
Research Directorate  
US Army Missile Laboratory

27 January 1982

*Approved for public release; distribution unlimited.*



**U.S. ARMY MISSILE COMMAND**

**Redstone Arsenal, Alabama 35809**

DTIC FILE COPY

**DTIC  
ELECTE  
JUN 29 1982**  
**S D**  
**B**

**82 06 28 110**

#### **DISPOSITION INSTRUCTIONS**

**DESTROY THIS REPORT WHEN IT IS NO LONGER NEEDED. DO NOT  
RETURN IT TO THE ORIGINATOR.**

#### **DISCLAIMER**

**THE FINDINGS IN THIS REPORT ARE NOT TO BE CONSTRUED AS AN  
OFFICIAL DEPARTMENT OF THE ARMY POSITION UNLESS SO DESIGNATED  
BY OTHER AUTHORIZED DOCUMENTS.**

#### **TRADE NAMES**

**USE OF TRADE NAMES OR MANUFACTURERS IN THIS REPORT DOES  
NOT CONSTITUTE AN OFFICIAL INDORSEMENT OR APPROVAL OF  
THE USE OF SUCH COMMERCIAL HARDWARE OR SOFTWARE.**

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER RR-82-2	2. GOVT ACCESSION NO. AD-A116 283	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) FABRICATION OF HOLOGRAPHIC OPTICAL ELEMENTS FOR ACHROMATIC MATCHED FILTERING SYSTEM		5. TYPE OF REPORT & PERIOD COVERED Technical Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) T. G. Georgekutty J. G. Duthie		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Commander, US Army Missile Command ATTN: DRSMI-RR Redstone Arsenal, AL 35898		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Commander, US Army Missile Command ATTN: DRSMI-RPT Redstone Arsenal, AL 35898		12. REPORT DATE 27 January 1982
		13. NUMBER OF PAGES 8
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Uncl
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Holography Optical Data Processing Achromatic Transforms Matched Filtering		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  Holographic optical elements such as lenses, gratings and holographic matched filters were fabricated for an anchromatic matched filtering system. Diffraction efficiencies of more than 90% were obtained in all these elements. These holographic elements were used in the achromatic matched filtering system and achromatic Fourier transforms were obtained. Experimental details involved in all these methods are briefly described.		

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

**SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)**



**SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)**

# CONTENTS

	Page No.
I. INTRODUCTION. . . . .	3
II. GRATING . . . . .	4
III. LENS . . . . .	4
IV. HOLOGRAPHIC MATCHED FILTER. . . . .	5
V. ACHROMATIC MATCHED FILTERING SYSTEM . . . . .	6
REFERENCES. . . . .	9



Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

## I. INTRODUCTION

In the achromatic matched filtering system, the following holographic optical elements are used (see figure 1): (a) two gratings of 2-inch diameter and spatial frequency of 1000 lines/mm; (b) two lenses of 2-inch diameter, 15-inch focal length and spatial frequency of 500 lines/mm; and (c) a matched filter of some test targets.




Figure 1

These elements were fabricated on dichromatin gelatin emulsion basically prepared from Kodak 649F standard and microflats of 4- x 5-inch size. Processing of the plates was done as outlined in Reference 4. Diffraction efficiency of more than 90% was obtained. These elements were then cemented together using the procedure mentioned in Reference 4. No degradation in the diffraction efficiency of these elements was found after the cementing. These elements were used in the achromatic matched filtering system (figure 1), and achromatic Fourier transforms were obtained as shown in figure 2. High efficiency matched filters for various test targets were fabricated and used in the system but good correlation was not obtained.




Figure 2



## II. GRATING

Phase gratings of very high diffraction efficiency were fabricated by recording the interference pattern between two plane waves from an Argon Ion laser. The angle between the two waves was such that the interference pattern had an average spatial frequency of approximately 1000 lines/mm (including angle of  $30^\circ$ ). The arrangement was as shown in figure 3.

The coherent light source was an Argon Ion laser of 4 watts power operating at 514.5 nm. This wavelength was selected to match the prominent line in the mercury arc lamp which was being used in the matched filtering system. The laser had a stable output of 400 mw at 514.5 nm with a coherent stretcher in the cavity. This beam was split into two and focused at the holographic plate at an angle of  $30^\circ$ . The film plane (plate holder) was perpendicular to the bisector of the angle between the two beams. The pathlengths and intensities of these two beams were approximately equal. The patterns were recorded on 4- x 5-inch Kodak 649F standard and microflats sensitized in dichromatin gelatin. The processing of these plates were done as in Reference 4. Room humidity was nearly 40%. The individual beam intensities were approximately  $1.5 \text{ mw/cm}^2$  and a total intensity of  $3 \text{ mw/cm}^2$  at the plate. An exposure time of 50 sec ( $150 \text{ mj/cm}^2$ ) was found to give a diffraction efficiency of more than 90%. A 10% ammonium dichromate solution was used for sensitizing the plates. High diffraction efficiency plates were cemented together following the procedure mentioned in Reference 4.

## III. LENS

The optical system is shown in figure 4. The Argon Ion laser was operating at 514.5 nm. In one path the pinhole spatial filter assembly (20X microscope objective and  $15\mu$  pinhole) was kept at a distance of 15" from the plate holder which acted as the object beam and the plate holder was kept perpendicular to this beam. The included angle between the two beams is  $15^\circ$ . The pathlengths and the beam ratio of the beams was made approximately equal. A power density of  $1.5 \text{ mw/cm}^2$  was obtained for the individual beams giving a total of  $3 \text{ mw/cm}^2$  at the plate. An exposure time of 50 sec




Figure 3




Figure 4

(150 mj/cm<sup>2</sup>) was found to give a diffraction efficiency of more than 90%. Holographic lenses of 2" diameter 15" focal length were fabricated using dichromatin gelatin Kodak 649F 4- x 5-inch standard and microflat plates. These plates were demented together using microflats as cover plates following the procedure suggested in Reference 4. The gelatin was removed from used low efficiency microflats by keeping them overnight in a solution of sodiumhydroxide and these microflats were used as cover plates.

#### IV. HOLOGRAPHIC MATCHED FILTER

Figure 5 is a schematic of the optical system used for making a holographic matched filter.  $L_1$  and  $L_3$  are collimating lenses of 78mm diameter and 381mm focal length. The object is a photographic image (5 x 5mm size) of a tank taken on 649F plate. The lens  $L_2$  is 78mm diameter and 381mm focal length takes the Fourier transform of the coherent image and displays it at the back focal plane of the lens. A holographic matched filter is recorded with this system located at the Fourier transform plane. A dichromatin gelatin plate with 10% concentration is used as the recording medium. The power density of both beams were made approximately equal and a number of exposures with various energy levels from 90 mj/cm<sup>2</sup> to 900 mj/cm<sup>2</sup> were made. A number of high efficiency matched filters were obtained and matched filters of various test targets were fabricated.





Figure 5

#### V. ACHROMATIC MATCHED FILTERING SYSTEM

Figure 1 is a schematic of the achromatic matched filtering system used in the laboratory experiments. A Mercury arc lamp is used as the light source and a  $25\mu$  pinhole kept at the focusing point acts as a point light source.  $L_1$  and  $L_2$  are the 2" diameter holographic lenses of 15" focal length fabricated on Kodak 649F microflats and  $G_1$  is the diffraction grating. A stop is kept in the path to block the direct beam. All these holographic optical elements were of high diffraction efficiency of more than 90%. The achromatic Fourier transforms obtained without the input is shown in figure 2 whereas figure 6 shows the Fourier transform of the system without using the holographic optical elements.

For the correlation studies, the holographic matched filter was placed exactly at the Fourier plane and precision adjustments were made but it failed to produce good correlation.



*Figure 6*

#### REFERENCES

1. Chang, B. J. and C. D. Leonard, "Dichromated Gelatin for the Fabrication of Holographic Optical Elements," Applied Optics, Vol. 18, No. 14/2407.
2. Liu, L. H., "Hologram Formation in Hardened Dichromated Gelatin Films," Applied Optics, 1969, pp. 963-966.
3. Guenther, B. D. and C. D. Leonard, Holographic Optics for Missile Guidance Systems, US Army Missile Research and Development Command, Redstone Arsenal, Alabama, Technical Report T-79-12.
4. Leonard, C. D. and B. D. Guenther, A Cookbook for Dichromated Gelatin Holograms, US Army Missile Research and Development Command, Redstone Arsenal, Alabama, Technical Report T-79-17.
5. Chang, B. J., "Dichromated Gelatin as a Holographic Storage Medium," SPIE, Vol. 177, 1979, pp. 71-81.

# DISTRIBUTION

	No. of Copies
Commander US Army Research Office ATTN: DRXRO-PH, Dr. R. Lentz Research Triangle Park, NC 27709	5
US Army Research and Standardization Group (Europe) ATTN: DRXSN-E-RX, LTC D. R. Reinhard Box 65 FPO New York 09510	1
Commander US Army Materiel Development and Readiness Command ATTN: Dr. James Bender Dr. Gordon Bushey 5001 Eisenhower Avenue Alexandria, VA 22333	1 1
Headquarters, Department of the Army Office of the DCS for Research, Development & Acquisition ATTN: DAMA-ARZ Room 3A474, The Pentagon Washington, DC 20301	1
OUSDR&E Room 3D1079, The Pentagon Washington, DC 20301	1
Director Defense Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, VA 22209	1
OUSDR&E ATTN: Dr. G. Gamota Deputy Assistant for Research (Research in Advanced Technology) Room 3D1067, The Pentagon Washington, DC 20301	1
Director of Defense Research and Engineering Engineering Technology Washington, DC 20301	2
Director Defense Advanced Research Projects Agency/STO ATTN: Commander T. F. Wiener D. W. Walsh 1400 Wilson Boulevard Arlington, VA 22209	1 1

Commander US Army Aviation Systems Command 12th and Spruce Streets St. Louis, MO 63166	1
Director US Army Air Mobility Research & Development Laboratory Ames Research Center Moffett Field, CA 94035	1
Commander US Army Electronics Research & Development Command ATTN: DRSEL-TL-T, Dr. Jacobs	1
DELEW-F, Henry E. Sonntag	1
Fort Monmouth, NJ 07703	
Director US Army Night Vision Laboratory ATTN: John Johnson	1
John Deline	1
Peter VanAtta	1
Fort Belvoir, VA 22060	
Commander US Army Picatinny Arsenal Dover, NJ 07801	1
Commander US Army Harry Diamond Laboratories 2800 Powder Mill Road Adelphi, MD 20783	1
Commander US Army Foreign Science and Technology Center ATTN: W. S. Alcott	1
Federal Office Building 220 7th Street, NE Charlottesville, VA 22901	
Commander US Army Training and Doctrine Command Fort Monroe, VA 22351	1
Director Ballistic Missile Defense Advanced Technology Center ATTN: ATC-D	1
ATC-O	1
ATC-R	1
ATC-T	
P. O. Box 1500 Huntsville, AL 35808	

Commander US Naval Air Systems Command Missile Guidance and Control Branch Washington, DC 20360	1
Chief of Naval Research Department of the Navy Washington, DC 20301	1
Commander US Naval Air Development Center Warminster, PA 18974	1
Commander US Naval Ocean Systems Center Code 6003 Dr. Harper Whitehouse San Diego, CA 92152	1
Director Naval Research Laboratory ATTN: Dave Ringwolt Code 5570, T. Gialborinzi Washington, DC 20390	1 1
Commander Rome Air Development Center US Air Force ATTN: James Wasielewski, IRR Griffiss Air Force Base, NY 13440	1
Commander US Air Force, AFOSR/NE ATTN: Dr. J. A. Neff Building 410 Bolling Air Force Base Washington, DC 20332	1
Commander US Air Force Avionics Laboratory ATTN: D. Rees W. Schoonover Dr. E. Champaign Dr. J. Ryles Gale Urban David L. Flannery Wright-Patterson Air Force Base, OH 45433	1 1 1 1 1 1
Commander AFATL/LMT ATTN: Charles Warren Eglin Force Base, FL 32544	1



Environmental Research Institute of Michigan  
Radar and Optics Division

ATTN: Dr. A. Kozma  
Dr. C. C. Aleksoff  
Juris Upatnieks

1  
1  
1

P. O. Box 8618  
Ann Arbor, MI 41807

IIT Research Institute  
ATTN: GACIAC  
10 West 35th Street  
Chicago, IL 60616

1

Dr. J. G. Castle  
9801 San Gabriel, NE  
Albuquerque, NM 87111

1

Commander  
Center for Naval Analyses  
ATTN: Document Control  
1401 Wilson Boulevard  
Arlington, VA 22209

1

Dr. J. W. Goodman  
Information Systems Laboratory  
Department of Electrical Engineering  
Stanford University  
Stanford, CA

1

Eirc G. Johnson, Jr.  
National Bureau of Standards  
325 S. Broadway  
Boulder, CO 80302

1

Dr. Nicholas George  
The Institute of Optics  
University of Rochester  
Rochester, NY 14627

1

Naval Avionics Facility  
Indianapolis, IN 46218

1

Dr. David Cassasent  
Carnegie Mellon University  
Hamerschage Hall, Room 106  
Pittsburg, PA 15213

1

Professor Anil K. Jain  
Department of Electrical Engineering  
University of California, Davis  
Davis, CA 95616

1

Terry Turpin  
Department of Defense  
9800 Savage Road  
Fort George G. Meade, MD 20755

1

Dr. William P. Bleha Liquid Crystal Light Valve Devices Hughes Aircraft Company 6155 El Camino Carlsbad, CA 92008	1
Dr. F. T. S. Yu Penn State University Department of Electrical Engineering University Park, PA 16802	1
US Army Night Vision Laboratory ATTN: DELNV-L, Dr. R. Buser Fort Belvoir, VA 22060	1
Dr. Stuart A. Collins Department of Electrical Engineering Ohio State University 1320 Kennear Road Columbus, OH 43212	1
US Army Materiel Systems Analysis Activity ATTN: DRXSY-MP Aberdeen Proving Ground, MD 21005	1
DRCPM-PE-E, John Pettitt	1
-PE	1
DRSMI-LP, Mr. Voigt	1
-R	1
-RN, Jerry Hagood	1
-RE, W. Pittman	1
-RD	3
-RG	1
-RG, J. A. McLean	1
-O	1
-Y	1
-RR, Dr. R. L. Hartman	1
Dr. J. S. Bennett	1
Dr. C. R. Christensen	1
Dr. J. G. Duthie	80
-RPR	15
-RPT, Record Copy	1
Reference Copy	1

